

Armourplan PVC Sealant

Termination Detail Sealant

Product Details

Material	Silicone Sealant
Cartridge Size	310ml
Colour	White / Grey
Product Number	47001001 / 47001002



Introduction

Armourplan PVC sealant is a single part neutral cure silicone sealant designed to be used with Armourplan membranes, which cures on exposure to moisture vapour forming an elastic silicone rubber. Armourplan PVC sealant is suitable for use in conjunction with most common building materials and is intended for use when terminating membrane pipe details and other upstand details in accordance with IKO Polymeric recommendations.

Features & Benefits

- Rapid Curing
- Cold Application
- Excellent adhesion properties
- Fast installation
- Cost effective application

Armourplan PVC Sealant Use

1. Ensure joint surfaces are clean, dry and free from contamination. No specialist cleaning or priming of the Armourplan membrane is required prior to application
2. Insert the cartridge into a suitable applicator and cut the end of the application nozzle to form the correct bead size.
3. Apply the sealant in an even and consistent bead and finish accordingly.

Important: Armourplan PVC Sealant must only be applied in temperatures above 5 Deg C.

Storage

Armourplan PVC Sealant should be stored in the original sealed container in dry conditions out of direct sunlight at a temperature between 5°C and 25°C. Shelf life is 12 months in an unopened container when stored at the above temperature.

IKO Polymeric

Coney Green Business Park, Coney Green Road
 Clay Cross, Chesterfield, S45 9HZ

T: 01257 488000
 F: 01246 861426

sales-ikopolymeric@ikogroup.co.uk
 technical-ikopolymeric@ikogroup.co.uk

Typical Properties

Characteristic properties	IKOpro High Performance PU Adhesive
Base	Neutral Cure Silicone
Skin Time	10 Minutes @ 20 °C, 65% RH
Cure Rate	2mm per 24 hrs @ 20 °C, 65% RH
Colour	Grey / White
Application Temperature	5 – 40 °C
Service Temperature	-40 – 120 °C
Shelf Life	12 months
Typical Shore A Hardness	30

Coverage Rates

Joint Size Suitability

Width – Minimum 6mm, maximum 25mm (single application) 50mm (multiple applications)

Depth – Minimum 10mm (porous substrates) 6mm (non-porous substrates), maximum 15mm

Joint Size (mm)	Coverage per Litre (l/m)	Coverage per Cartridge (l/m)
6 x 6	27.8	8.6
9 x 6	18.5	5.7
12 x 6	9.3	2.9
18 x 10	5.6	1.7
25 x 10	4.0	1.2

Further Product Information

Full product literature, health & safety and technical sheets are available as downloads from our website: www.ikogroup.co.uk or on request by email: marketing@ikogroup.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.

Company Registered in England No. 2678296 – Registered Office: Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB



NSFPlus

IKO Polymeric

Coney Green Business Park, Coney Green Road
Clay Cross, Chesterfield, S45 9HZ

T: 01257 488000
F: 01246 861426

sales-ikopolymeric@ikogroup.co.uk
technical-ikopolymeric@ikogroup.co.uk